

**1 D+H Mechatronic (english)****1.1 VCD Series - Drives****1.1.1 Chain drive - VCD 204/350-Z-TMS+-A (SR)****24 V DC / 0.35 A / 200 N / 350 mm stroke****Performance features:**

Electromotive drive unit for opening and closing of windows and flaps for daily ventilation. The drive is equipped with motor electronics controlled via microprocessor. TMS+" tandem safety function for operating 2 drives on one sash. Learning with magnet will be transmitted to dual drive. Option of chain stroke programming via magnet. The drive is equipped with a special chain stabilisation and centred chain outlet. Cut-off force in CLOSED-direction is electronically reduced to 150 N at the factory. Running speed in CLOSED direction decreases to 5 mm/s (passive closing edge protection). Time-controlled reversing when an obstacle is detected in the CLOSED direction (active closing edge protection). Electronic limit stop and overload cut-off is integrated.

**Technical data:**

Operating voltage: 24 V DC /  $\pm 20\%$   
Current consumption: 0.35 A  
Duty cycle: 30 % (ON: 3 min. / OFF: 7 min.)  
Force of pressure: 200 N  
Tensile force: 200 N  
Nominal locking force \*\*: 2000 N  
Service life: 20000 double strokes \*  
Stroke length: 350 mm  
OPEN running speed: 6 mm/s  
CLOSED running speed: 6 mm/s  
Type of protection: IP 30  
Emission sound pressure level:  $L_pA \leq 46$  dB(A)  
Temperature range: 0 °C till +60 °C  
Drive: Push link chain  
Housing: Die-cast zinc  
Surface: Powder-coated  
Colour: Silver (~ RAL 9006)  
Connection: 2.5 m PVC-cable  
Dimensions (WxHxD): 480 x 30 x 47 mm

\* For vertical use, please consult with D+H Sales!

\*\* Depending on the mounting

**Scope of supply:**

Drive unit with 1.2 m connecting cable, instruction for use

Brand: D+H Mechatronic AG

Type: Chain drive -

[Planning Support](#)

**Artikelnr.:** 25.121.35

**Quantity:** ..... Stk    **Preis:** ..... €    **TP:** ..... €