

- 1 D+H Mechatronic (english)**
- 1.1 ZA Series - PLP drives**
- 1.1.1 PLP rack and pinion drive - ZA-0300-0600-1-PLP-R**

**24 V DC / 0.5 A / 300 N / 600 mm stroke**

**Performance features:**

Electromotive drive unit for opening and closing of windows, flaps and skylights. The drive is equipped with motor electronics controlled via microprocessor. Programmable drive functions (stroke limitation, force, speed) and performance features on site via Powerline (PLP) and the D+H software SCS. Can be used for openings for smoke exhaust; D+H Euro SHEV in accordance with EN 12101-2; and for daily ventilation. Particularly quiet drive in ventilation mode due to reduced running speed. Electronic limit stop and overload cut-off protect the element and the drive from damage. The power supply can be connected either from below or above. The drive unit can also be changed from left to right.

**Technical data:**

Operating voltage: 24 V DC /  $\pm 15\%$   
Current consumption: 0.5 A  
Duty cycle: 30 % (ON: 3 min. / OFF: 7 min.)  
Force of pressure: 300 N (note pressure load diagram)  
+ 20 % cut-off reserve (temporary)  
Tensile force: 300 N  
Nominal locking force \*\*: Max. 1400 N (1100 N \*\*\*)  
Service life: > 20000 double strokes \*  
Stroke: 600 mm  
OPEN running speed: 7.1 mm/s  
OPEN running speed - SHEV: 8 mm/s  
CLOSED running speed: 7.1 mm/s  
Type of protection: IP 65  
Emission sound pressure level:  $L_pA \leq 51$  dB(A)  
Temperature range: -15 °C (-5 °C \*\*\*) till +75 °C  
Fire resistance: B300 (30 min / 300 °C)  
Opening mechanic: Stainless steel rack (V2A), maintenance -free  
Tube: Aluminium, powder-coated, white aluminium (~ RAL 9006)  
Housing motor: Polycarbonate, grey (~ RAL 7035)  
Connection: 2.5 m silicone cable  
Dimensions (WxHxD):  
Tube 762 x 30 x 30 mm  
Housing motor 160 x 104 x 46 mm  
Re = 1000 double strokes  
Le = 20000 double strokes \*

\* For vertical use, please consult with D+H Sales!

\*\* Depending on the mounting

\*\*\* In accordance with VdS 2580

**Scope of supply:**

Drive unit with 2.5 m silicone connection cable, eyebolt (6 mm eye), instruction for use

Brand: D+H Mechatronic AG

Type: ZA-0300-0600-1-PLP-R

[Planning Support](#)

**Artikelnr.:** 27.005.15

**Quantity:** ..... **Stk**    **Preis:** ..... **€**    **TP:** ..... **€**