

- 1 D+H Mechatronic (english)**
- 1.1 VCD Series - ACB Drives**
- 1.1.1 ACB chain drive - VCD-0203-1-ACB - freely configurable**

24 V DC / Special production according to customer requirements

Electromotive drive unit with Modbus RTU interface for surfaced mounting at the window profile. For the comfortable electromotive opening and closing of bottom hung-, top hung-, parallel opening-, and trapezoidal windows in the facade, as well as for roof windows. Useable for daily ventilation mode. Compatible to D+H locking drives.

Performance features:

Integrated Advanced Communication Bus (ACB) with open Modbus RTU protocol;
High-precise motor- and synchron electronic for parallel run for up to 8 drives;
Connection of up to 4 locking drives;
Corrosion protected, hardened, rigid backing steel chain, maintenance free by lifetime lubrication;
Special chain stabilization;
Active and passive locking edge protection;
Various adjustable drive parameters (stroke, force, speed);
Gasket protection thanks to the automatic relief of pressure on window gasket after a closing process;
Easy installation thanks to polarity reversal protection connector system;
Individual parameterizing via D+H software SCS;
Low operation noises;

Functional description ACB

Direct integration of drive by open Modbus RTU bus-communication via Advanced Communication Bus (ACB) for the building automation, e.g. in BMS (building management system) with following features:

- Exact position operating (relative values, in 1% steps)
- Creation of virtual groups at one output
- OPEN and CLOSED-indication (incl. locking drive)/ group signal
- Monitoring of connected drives
- Status monitoring of motor
- Diagnostic and parameterizing directly via controller
- Modbus protocol "ACB planning manual" as download link on D+H's website
- Max. 32 ACB-bus-participants at Modbus RTU

Technical data:

Operating voltage: 24 V DC / ± 20 %
Current consumption: 0.35 A
Duty cycle: 30 % (ON: 3 min. / OFF: 7 min.)
Shutdown: Integrated electronic load cut-off
Configuration: **Main or Sub**
Design: Right
Force of pressure: 200 N
Tensile force: 200 N
Nominal locking force **: 2000 N / 4000 N ***
Service life: 20000 double strokes *
Stroke length: 250 mm
OPEN running speed: 6 mm/s
CLOSED running speed: 6 mm/s (according to protection class 3, Machinery Directive 2006/42/EG)
Type of protection: IP 30
Emission sound pressure level: $L_p A \leq 46$ dB(A)
Temperature range: 0 °C till +60 °C

Opening mechanic: Maintenance-free, corrosion protected hardened push linked chain with lifetime lubrication
Housing: two-part, die-cast zinc
Surface: **on request**
Colour: **on request**
Connection: PVC-cable
Dimensions (WxHxD): 300 x 30 x 47 mm

- * For vertical use, please consult with D+H Sales!
- ** Depending on the mounting
- *** Optionally increased nominal locking force

Scope of supply:

Drive unit with PVC connection cable with system plug, instruction for use

Brand: D+H Mechatronic AG

Type: VCD-0203-1-ACB

The D+H partner on site is at your disposal for design variants.

[Planning Support](#)

Artikelnr.: 25.155.10

Quantity: Stk **Preis:** € **TP:** €