

- 1 **D+H Mechatronic (english)**
- 1.1 **SHD Series - Drives**
- 1.1.1 **BSY+ side-hung vent drive - SHD 54/450-BSY+ (M2)**

**24 V DC / 1 A / 500 N / 450 mm stroke**

**Performance features:**

Electromotive drive unit for opening and closing of side-hung vent windows;  
The drive is equipped with motor electronics controlled via microprocessor;  
Drive functions and performance features are individually programmable;  
Can be used for openings for smoke exhaust; D+H Euro SHEV in accordance with EN 12101-2;  
and for daily ventilation;  
Particularly quiet drive in daily ventilation mode;  
For sash sizes up to 1.2 x 2 m;  
Opening the windows to 65° in less than 30 sec.;  
Electronic limit stop and overload cut-off;  
With integrated force and position control;  
Special chain stabilisation;  
Locking mechanism for the window in conjunction with window locking drive (optional);

**Technical data:**

Operating voltage: 24 V DC /  $\pm 15\%$   
Current consumption: 1 A  
Duty cycle: 30 % (ON: 3 min. / OFF: 7 min.)  
Configuration: Main 2  
Force of pressure: 500 N  
Tensile force: 500 N  
Service life: 20000 double strokes  
Stroke length: 450 mm  
OPEN running speed: 11.8 mm/s.  
OPEN running speed - SHEV: 15.2 mm/s  
CLOSED running speed: 11.8 mm/s  
Type of protection: IP 50  
Emission sound pressure level:  $L_pA \leq 70$  dB(A)  
Temperature range: -15 °C (-5 °C \*) till +75 °C  
Fire resistance: B300 (30 min / 300 °C)  
Housing: Aluminium  
Surface: Powder-coated  
Colour: White aluminium (~ RAL 9006)  
Connection: 2.5 m silicone cable  
Dimensions (WxHxD): 500 x 40 x 115 mm

\* In accordance with VdS 2580

**Scope of supply:**

Drive unit with 2.5 m silicone connection cable, incl. bracket set, instruction for use

Brand: D+H Mechatronic AG  
Type: SHD 54/450-BSY+ Set

[Planning Support](#)

**Artikelnr.:** 23.050.81

**Quantity:** ..... **Stk**    **Preis:** ..... **€**    **TP:** ..... **€**

