

**1 D+H Mechatronic (english)****1.1 Expansion Modules****1.1.1 ACB interface module - ACB-BSY+-GW1-230****ACB interface module for 230 V AC BSY+ drives****Performance features:**

Interface module between building management system or D+H control panel (CPS-M1) and a 230 V AC BSY+ drive group;  
Expands the drive functions, for example, to include functions of precise position control and virtual group formation;  
Enables the use of real drive positions, for example, for OPEN and CLOSED signals;  
Fault message of the individual BSY+ group;  
No special drive notification or configuration required;  
Galvanic isolation between the input signal and output signal;  
For installing on-site junction box;  
Galvanic isolation between both connection terminals;

**Technical data:**

Operating voltage: 24 V DC / ±15 %  
Stand-by power: 0.24 W  
ACB input: Modbus RTU  
Data output: BSY+  
Wire cross section: max. 1.5 mm<sup>2</sup>  
Type of protection: IP 30  
Temperature range: -5 °C till +75 °C  
Housing: Plastic material  
Connection: Push-in terminals  
Dimensions (WxHxD): 50 x 48 x 19 mm

**Scope of supply:**

Module, instruction for use

Brand: D+H Mechatronic AG

Type: ACB-BSY+-GW1-230

[Planning Support](#)

**Artikelnr.:** 30.555.20

**Quantity:** ..... Stk    **Preis:** ..... €    **TP:** ..... €