

- 1 D+H Mechatronic (english)**
- 1.1 DAC-M Series - ONLY FOR FRANCE**
- 1.1.1 SHEV control panel - compact - DAC 4408-M**

**24 V DC / 8 A / 2 lines / 2 drive groups****Performance features:**

SHEV control - AdComNet ready;  
Approval according to EN 12101-10 and certified according to NF 537, developed according to ISO 21927-9;  
Stabilised output voltage;  
Connection of up to 4 SHEV operation panels per control panel;  
Min. 72 hr battery backup supply;  
Temperature-controlled battery charge;  
Batterie charge and status check;  
SHEV retriggering function;  
Codable SHEV and ventilation functions;  
Combination of a SHEV- / building alarm function possible;  
Comfort ventilation functions;  
Line monitoring for short circuit and interruption;  
Slot for additional module;  
Possible connection for optical and acoustical alarm devices;  
LED status display visible from outside;  
Usable for daily ventilation;  
Ventilation time and opening width adjustable;  
Wind/rain sensor connectable without additional module;

**Technical data:**

Supply: 230 V AC / 50 Hz / 240 VA  
Stand-by power: 4.5 W / 7 VA  
Output: 24 V DC (21.6 - 28.5 V DC) / 8 A  
Ripple: < 2 Vss  
Mode of operation  
-Monitoring: Continuous duty  
-Alarm / Ventilation: Short-time duty (30 % duty cycle)  
Type of protection: IP 32D  
Temperature range: -5 °C till +40 °C  
Line / Group: 2 / 2  
Housing: Plastic with steel sheet door  
Colour: White (~ RAL 9016)  
Dimensions (WxHxD): 310 x 310 x 100 mm

**Scope of supply:**

Control panel with plastic housing with steel sheet door incl. keys, without batteries (batteries must be ordered separately)

Brand: D+H Mechatronic AG

Type: DAC 4408-M

[Planning Support](#)

**Artikelnr.:** 30.118.60

**Quantity:** ..... **Stk**    **Preis:** ..... **€**    **TP:** ..... **€**