

# CPS-B1-2.5-0101



## Performance features

- + Compact SHEV control panel, specifically for stairwells
- + Integrated comfort functions for daily ventilation
- + Tested and certified according to ISO 21927-9, VdS 2581, VdS 2593, VdS 2344, DIN EN 12101-10 and EN 62368-1:2014 + A11:2017, fulfils the building authority requirements in accordance with DIN 18232-9
- + Optional connection to rain detectors or wind / rain sensors without an additional module
- + Up to 2.5 A total drive current
- + Connection of up to 8 SHEV operation panels and 8 fire detectors per line (Only detectors permitted by D+H may be used)
- + Stabilised output voltage
- + Min. 72 hr battery backup supply
- + Switchable SHEV safety functions: Fault equal to alarm, SHEV retriggering function and smoke detector remote reset

## Approvals / Certificates

Find out about permission details from your D+H Partner.



# Technical data

CPS-B1-2.5-0101

<b>Supply</b>	230 V AC / 50 Hz / 140 VA
<b>Stand-by power</b>	< 2 W
<b>Output</b>	24 V DC / 2.5 A
<b>Mode of operation monitoring</b>	Continuous duty
<b>Mode of operation Alarm / Ventilation</b>	Short-time duty 30 % duty cycle
<b>Type of protection</b>	IP 30
<b>Temperature range</b>	-5 °C ... +40 °C
<b>Line / Group</b>	1 / 1
<b>Housing</b>	Plastic
<b>Colour</b>	White (~ RAL 9016)
<b>W x H x D</b>	310 x 310 x 104 mm
<b>Battery type</b>	Typ 2 (2x)
<b>Weight</b>	1.87 kg
<b>Art. No.</b>	30.119.10

Batteries must be ordered separately.

## Example of application

