

# GVL 8401-K-RC V2



## Performance features

- + Compact ventilation control panels with an integrated wireless receiver for controlling 24 V DC window drives
- + Up to 1 A total drive current
- + 2 ventilation groups
- + Optional individual and/or control circuit (OPEN / CLOSED)
- + Configurable ventilation safety function (storage operation OPEN / CLOSED)
- + Freely programmable group assignment for central inputs (weather, time, etc.)
- + Operation via wireless remote control (Multiple control panels can be controlled with one remote control)
- + 868 MHz radio frequency, permitted throughout the EU
- + High level of security against external control - 24 bit address code and transmitting code change at each button press (hopping code)

# Technical data

## GVL 8401-K-RC V2

<b>Supply</b>	230 V AC / 50 Hz / 56 VA
<b>Stand-by power</b>	< 1 W
<b>Output</b>	24 V DC / 1 A
<b>Mode of operation</b>	Short-time duty 20 % duty cycle
<b>Type of protection</b>	IP 66
<b>Temperature range</b>	-5 °C ... +40 °C
<b>Group(s)</b>	2
<b>Housing</b>	Polypropylene
<b>Colour</b>	Light grey (~ RAL 7035)
<b>W x H x D</b>	180 x 130 x 77 mm
<b>Weight</b>	0.97 kg
<b>Art. No.</b>	30.241.90

## Example of application

